


DALI  
Dimmable

Dimmable

Dimmable  
0/1...10

Part Number	Output V	Ouput@230V I max	W @230V	Ouput@110V I max	W @110V	Dimensions A x B x C	Protocol
A40PBX75D48B	48V	1,56A	75W	1,04A	50W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH
A40PBX10D48B	48V	2,08A	100W	1,25A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH
A40PBX15D48B	48V	3,12A	150W	1,25A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH



Datasheet download

### Alimentatore LED 48V dimmerabile DALI/0-10V/1-10V/Push

- Alimentatore indipendente - IP20 - Classe II di isolamento
  - Comando DALI o pulsante (sul secondario, con memoria), 0-10V, 1-10V o potenziometro, selezionabile tramite impostazione dip-switches.
  - Possibilità di sincronizzare più alimentatori
  - Uscita in tensione costante 48V PWM
  - Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
  - Morsetti rapidi
  - Doppio collegamento di uscita
  - Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
  - Alimentazione: 110÷240V/AC - Uscita stabilizzata.
- A richiesta, alimentazione a 230VDC o specifica potenziata a 110V

### 48V dimmable LED Driver DALI/0-10V/1-10V/Push

- For independent use - IP20 - Insulation class II
  - Dimming control by DALI or PUSH (on the secondary, with memory), 0-10V, 1-10V or potentiometer, selecting the dipswitch combination on board.
  - Possible synchronization of more drivers
  - Output in constant voltage 48V PWM
  - Self-resetting protection against overtemperatures, open circuit and against output short circuits
  - Fast terminals
  - Double output.
  - Cable clamp for flat and round cables
  - Input voltage: 110÷240V/AC - Steady output.
- On request, 230VDC input voltage or specific boosted 110V version