


# Nike



Ø 17mm



<b>POWER SUPPLY</b>	max 1W - max 350mA															
<b>CODE</b>	NKM01 ■ ■ ■															
<b>LED COLOUR</b>	C - Cool white 5500°K N - Natural white 4000°K W - Warm white 3000°K H - Warm white 3000°K - CRI90 Y - Warm white 2700°K A - Amber															
<b>OPTICS</b>	<table border="0"> <tr> <td>M</td> <td>W</td> <td>X</td> <td>E</td> <td>D</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>20°</td> <td>35°</td> <td>50°</td> <td>20°x45°</td> <td>Diff.</td> </tr> </table>	M	W	X	E	D						20°	35°	50°	20°x45°	Diff.
M	W	X	E	D												
20°	35°	50°	20°x45°	Diff.												
<b>FINISHES</b>	W - White G - Grey B - Black															
<b>LUMEN OUTPUT SOURCE</b>	110lm (3000°K, 350mA)															
<b>DELIVERED LUMEN OUTPUT</b>	100lm (3000°K, 350mA, 50°)															
<b>LED NUMBER</b>	1 power LED															
<b>MATERIAL</b>	body in anodized aluminium, flange in anodized or painted aluminium															
<b>DRIVER</b>	not included, see pag. 322 and 326															
<b>POWER CABLE</b>	includes 0,5 mt FEP 2 x 0,35 cable															
<b>WIRING</b>	in series															
<b>MOUNTING</b>	recessed (ceiling, wall, bottom up)															
<b>NOTES</b>	other RAL on request															