



MINIW-Z

Part Number	CCT (K)	Lumen Typ.	Beam	Lux @1m	I (Typ)	V (Typ)	W	Ø	EEC**
A40MINIWZ027	2700K	119	Wide 40°	135	350 mA	2,9V	1W	White	D
A40MINIWZ030	3000K	123	Wide 40°	144	350 mA	2,9V	1W	White	D
A40MINIWZ040	4000K	130	Wide 40°	148	350 mA	2,9V	1W	White	C
A40MINIWZ050	5000K	150	Wide 40°	165	350 mA	2,9V	1W	White	C
A40MINIWZ127	2700K	119	Wide 40°	135	350 mA	2,9V	1W	Transparent	D
A40MINIWZ130	3000K	123	Wide 40°	144	350 mA	2,9V	1W	Transparent	D
A40MINIWZ140	4000K	130	Wide 40°	148	350 mA	2,9V	1W	Transparent	C
A40MINIWZ150	5000K	150	Wide 40°	165	350 mA	2,9V	1W	Transparent	C
A40MINIWZ227	2700K	119	Wide 40°	135	350 mA	2,9V	1W	Black	D
A40MINIWZ230	3000K	123	Wide 40°	144	350 mA	2,9V	1W	Black	D
A40MINIWZ240	4000K	130	Wide 40°	148	350 mA	2,9V	1W	Black	C
A40MINIWZ250	5000K	150	Wide 40°	165	350 mA	2,9V	1W	Black	C
A40MINIWZ327	2700K	119	Wide 40°	135	350 mA	2,9V	1W	Titanium	D
A40MINIWZ330	3000K	123	Wide 40°	144	350 mA	2,9V	1W	Titanium	D
A40MINIWZ340	4000K	130	Wide 40°	148	350 mA	2,9V	1W	Titanium	C
A40MINIWZ350	5000K	150	Wide 40°	165	350 mA	2,9V	1W	Titanium	C
A40MINIWZ427	2700K	119	Wide 40°	135	350 mA	2,9V	1W	Chrome	D
A40MINIWZ430	3000K	123	Wide 40°	144	350 mA	2,9V	1W	Chrome	D
A40MINIWZ440	4000K	130	Wide 40°	148	350 mA	2,9V	1W	Chrome	C
A40MINIWZ450	5000K	150	Wide 40°	165	350 mA	2,9V	1W	Chrome	C

** The EEC specification refers in each case to the installed light source(s)

🇮🇹 Spot a LED di potenza - 350mA

- Resa luminosa 119÷150lumen
- Si monta a pressione in un foro da Ø 24mm
- Fornito con cavo da 0,3 m e connettore MiniAmp.
- Disponibile nei colori 2700K, 3000K, 4000K e 5000K

🇬🇧 High Brightness LED spot - 350mA

- Light power 119÷150 lumen
- Pressure assembly into a Ø 24mm hole
- Supplied with 0,3 m cable and Mini Amp connector
- Color temperatures available: 2700K, 3000K, 4000K and 5000K

