

12
Watt/m

IP 67

CRI>90



ta -20°÷ +40°C

Flame
resistant

UV
resistant

SALT
water



Part Number	CCT (K)	Lumen/m	LED/m	V (Typ)	Cut	W/m	IP
A41SPIN12030	3000K	250	120	24VDC	50mm	12W	IP67
A41SPIN12040	4000K	290	120	24VDC	50mm	12W	IP67

Ø>80mm



SISTEMI DI CONTROLLO SUGGERITI:
 RECOMMENDED CONTROL SYSTEMS:



Codice/Code: **A40SPI03000B**
RF receiver 2,4 GHz
Page: 204



Codice/Code: **A40WALLWP86K**
RF controller 2,4 GHz
Page: 203



Datasheet download

Strisce flessibili NEON DIGITAL SPI a 24V - IP67

- LED 2835 ad alta efficienza e a bassa caduta di tensione
- Strip led digitali che, grazie alla tecnologia IC pixel-to-pixel, permettono di creare effetti di luce avanzati
- 120led/m - 12W/m
- Densità LED: 20 pixels per metro (1 IC per segmento 6 led)
- IC/UCS1903H
- Disponibile nei colori standard 3000K e 4000K
- Fornite in nastro da 5m e cavetto di raccordo.

24V Flexible NEON DIGITAL SPI LED strips - IP67

- LED 2835 with high lumen efficiency and low voltage drop
- Digital Led strips that thanks to pixel-to-pixel IC technology allow to create advanced light effects.
- 120led/m - 12W/m
- LED density: 20 pixels per meter (6leds segment by 1 IC)
- IC/UCS1903H
- Available in standard 3000K and 4000K
- Supplied in 5m roll with connecting cable

