

DALI
DimmableDALI
Dimmable

| Part Number | Output V | Output@230V I max | W @230V | Dimensions A x B x C | Protocol |
|--------------|----------|-------------------|---------|----------------------|------------|
| A40CV23WD00B | 24V/DC | 80-960mA | 23W | 163 x 30 x 21 | DALI /PUSH |
| A40CV36WD00B | 24V/DC | 80-960mA | 36W | 163 x 30 x 21 | DALI /PUSH |



Datasheet download

- Alimentatore LED dimmerabile DALI/Push**
- Alimentatore indipendente - IP20 - Classe II di isolamento
 - Comando DALI o pulsante (con memoria)
 - Possibilità di sincronizzare più alimentatori
 - Uscita in tensione costante 24V PWM
 - Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
 - Morsetti rapidi
 - Alimentazione: 220÷240V/AC - Uscita stabilizzata.

- Dimmable LED Driver DALI/Push**
- For independent use - IP20 - Insulation class II
 - Dimming control by DALI or PUSH (memory function)
 - Possible synchronization of more drivers
 - Output in constant voltage 24V PWM
 - Self-resetting protection against overtemperatures, open circuit and against output short circuits
 - Fast terminals
 - Input voltage: 220÷240V/AC - Steady output.

